

# DATASHEET

## POWER REX

Fiberglass rod Ø 3 mm incl. RUNPOGLIDER

Item no.: 10087 | 10088 | 10089 | 10090



**VIDEO**

RUNPOGLEITER

Click here Video

Click here Productinformation

**INCLUDED ACCESSORIES**

**PATENTED**

**Achtung!** Stromleitend  
**Attention!** electric conductive

**INFORMATION**

**BEGINNING**

RUNPOGLIDER with swivel Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread, screwed to strand

**ENDING**

Endingjoint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

| DATA                |                                  |               |               |               |
|---------------------|----------------------------------|---------------|---------------|---------------|
| ITEM NO.            | 10087                            | 10088         | 10089         | 10090         |
| LENGTH              | 20 m                             | 30 m          | 40 m          | 50 m          |
| TOTAL WEIGHT        | 1,12 kg                          | 1,24 kg       | 1,34 kg       | 1,46 kg       |
| MATERIAL            | Fiberglass core with PP Sheath   |               |               |               |
| TOTAL BREAKING LOAD | 120 kg                           |               |               |               |
| BENDING RADIUS      | 55 mm                            |               |               |               |
| TUBE DIAMETER Ø     | for pipe dimension 16 mm - 50 mm |               |               |               |
| EAN-CODE            | 9120045473964                    | 9120045473971 | 9120045473988 | 9120045473995 |

- ADVANTAGES**
- ✓ RUNPOCAM RC 2-compatible
  - ✓ Shear-stable
  - ✓ Also for occupied pipes
  - ✓ Numerous accessories included
  - ✓ Patented RUNPOGLEITER with eyelet and integrated twist compensation
  - ✓ Total breaking load 120 kg

### Rec. tube diamter, bending radius and total breaking load of POWER REX Ø 3 mm

|      |          |       |        |        |
|------|----------|-------|--------|--------|
| Ø    |          |       |        |        |
| 3 mm | 16-50 mm | 55 mm | 450 Kg | 120 Kg |

**DESCRIPTION**

Power Rex - cable pulling device, glass fibre rod Ø 3 mm with end sleeve RUNPOTEC RTG Ø 6 mm thread and the patented RUNPOGLEITER with twist compensation in a practical plastic box The stated total breaking load of 120 kg always refers to the entire product (glass fibre rod including end sleeves). The POWER REX is a slide-in system further developed by RUNPOTEC, which scores with the revolutionary RUNPOGLEITER with twist compensation, a storage compartment for all accessories and high-quality workmanship. Better gliding, higher tensile load, extra large eyelet hole for more cable intake, no need to change the eyelet head. Excellent in combination with the RUNPOTEC RC 2 multifunctional camera.

**Optimal field of application:** for pipe dimensions 16 mm - 50 mm.

**Scope of delivery:** POWER REX in plastic box incl. RUNPOGLEITER with twist compensation at the rod tip and end sleeve with RUNPOTEC RTG Ø 6 mm thread at the rod end, 1 x pulling aid, 1 x special adhesive 3g, 1 x cable pulling sleeve 6 - 9 mm with twist compensation, 3 x connecting sleeves Ø 6 mm, 5 x end sleeves Ø 6 mm, 2 x pulling eyes Ø 7 mm

**INFORMATION**

**Compatible with:**

**RUNPOCAM RC2**

Length: 10 m | 30 m | 50 m  
Item no. 10139 | 10140 | 10141

Click here Productinformation