


DLPlus mini-trunking: profiles and accessories


| BODIES | SECTION | FINISHING ACCESSORIES | | | | | | |
|----------------------|----------------------------------|-----------------------|----------------|----------------|------------|-------------|-----------------|-------------------------|
| | | End cap | Internal angle | External angle | Flat angle | Cover joint | Flat T junction | Junction box |
| Size and shape | Length 2.10 m | | | | | | | |
| 20 x 12.5 | 0 300 07 0 300 08 6 489 05 | 0 312 02 | 0 302 21 | 0 302 21 | 0 302 23 | 0 336 02 | 0 302 24 | 0 303 16 ⁽¹⁾ |
| 32 x 12.5 | 0 300 14 0 300 15 | 0 312 03 | 0 302 51 | 0 302 51 | 0 302 53 | 0 336 03 | 0 302 54 | 0 303 16 |
| 32 x 16 | 0 308 04 6 489 06 | 0 312 07 | 0 333 25 | 0 333 25 | 0 333 27 | 0 336 04 | 0 333 30 | 0 303 16 |
| 40 x 20 | 0 300 27 | 0 312 11 | 0 302 81 | 0 302 81 | 0 302 83 | 0 336 06 | 0 302 08 | 0 303 16 |
| 60 x 20 | 0 301 14 | 0 302 90 | 0 302 91 | 0 302 92 | 0 302 93 | 0 336 08 | 0 302 09 | 0 303 16 |
| 75 x 20 | 0 300 33 | 0 303 00 | 0 303 01 | 0 303 02 | 0 303 03 | 0 336 09 | 0 302 18 | 0 303 16 |

1: Dimensions: 75 x 75 mm




Cable-grip

It makes the installation easier and faster by containing all the wires inside the trunking body before the cover is clipped



Comfortable implementation

- During installation, the conductors stay in place in the 1 or 2 compartment mini-trunking thanks to cable-grip membranes



Speed of installation

- Cable holding is integrated with the trunking (no staple to add)
- Easy conductors position
- Quick cover fitting