


# SENECA RECESSED

Dedicated LED emergency fittings for recessed mounting



SENECA RECESSED OVAL AND ROUND WITH MOUNTING DISC IN POSITION



SENECA RECESSED REAR VIEW



## APPLICATIONS

- Corridors
- Escape routes


## CONSTRUCTION

- Moulded polycarbonate body
- Acrylic lens
- Supplied with 140mm dia mounting disc - use optional depending on the diameter of the ceiling aperture. When removed diameter is only 85mm.
- NiCd battery pack (not suitable for use below 0°C)


## TECHNICAL DETAILS

- 2W Oval - 135 lumens
- 2W Wide - 140 lumens
- Non-maintained operation
- Choice of two lenses for different light distributions:
  - **Wide**, giving a circular distribution
  - **Oval**, giving an oval light distribution. (Suffix OVAL).
- Momentary manual test button fitted
- Self-test version, compliant with BS5266 available. Suffix STM3 as listed

**WIDE VERSION**  
Light distribution 360° symmetric.  
Suitable for open areas.



**OVAL VERSION**  
Light distribution elongated in one dimension,  
short in the other. Suitable for corridors.



ORDER CODE	DESCRIPTION
NSC2/LED/REC/NM3	Seneca 2W LED Non-Maintained Recessed
NSC2/LED/REC/STM3	Seneca 2W LED Non-Maintained Self Test Recessed
NSC2/LED/REC/OVAL/NM3	Seneca 2W LED Non-Maintained Recessed Oval Dist
NSC2/LED/REC/OVAL/STM3	Seneca 2W LED Non-Maint. Self Test Recessed Oval Dist

