




P3, 63 A, surface mounting

Part no. P3-63/I3
Catalog No. 207351

Delivery program

Product range			On-Off switch								
Part group reference			P3 with black thumb grip and front plate								
Information about equipment supplied			Auxiliary contact or neutral conductor fitted by user.								
Number of poles			3 pole								
Degree of Protection			IP65								
Design			surface mounting								
											
Contact sequence			<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>1</td> <td>X</td> <td>X</td> <td>X</td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> </table> <p style="text-align: center;">1 0 2 0 3 0 4 0 5 0 6 0</p>	1	X	X	X	0			
1	X	X	X								
0											
Motor rating AC-23A, 50 - 60 Hz											
400 V	P	kW	30								
Rated uninterrupted current	I_u	A	63								
Note on rated uninterrupted current I_u			Rated uninterrupted current I_u is specified for max. cross-section.								

Technical data

Contacts

Mechanical variables			
Number of poles			3 pole
Electrical characteristics			
Rated uninterrupted current	I_u	A	63
Note on rated uninterrupted current I_u			Rated uninterrupted current I_u is specified for max. cross-section.

Assets (links)

Declaration of CE Conformity

00003104

Instruction Leaflets

IL03801010Z2018_05

Additional product information (links)

Technical overview cam switch, switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.2
System overview cam switch T	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.4
System overview switch-disconnector P	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.6
Key to part numbers Cam switch	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Key to part numbers Switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Switches for ATEX	http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html