

# DATA SHEET

## FIBERGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double run-out system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



**VIDEO**  
Fiberglass rod Ø 4,5 mm  
[Click here Video](#)

[Click here Productinformation](#)

**INCL. ACCESSORIES**

**Achtung!** Stromleitend  
**Attention!** electric conductive

Detailed image

**BEGINNING**

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

**ENDING**

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA					
ITEM NO.	10052	10055	10057	10047	10050
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	for tube diameter 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

- ADVANTAGES**
- ✓ incl. steel reel
  - ✓ Double run-out system (automatic run-out brake and fast run-out)
  - ✓ Additional parking brake
  - ✓ Glass fibre rod total breaking load up to 1300 kg
  - ✓ Total breaking load 220 kg  
Bending radius 120 mm

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

**DESCRIPTION**

Professional set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

**Optimal field of application:** for pipe diameters 30 mm - 80 mm.

**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).

**Scope of delivery:** 1 piece fiberglass rod Ø 4.5 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

**INFORMATION**

**Compatible with:**  
**RUNPOCAM RC2**  
Length: 10 m | 30 m | 50 m  
Item no. 10139 | 10140 | 10141

[Click here Productinformation](#)

# DATA SHEET

## FIBERGLASS ROAD Ø 4,5 MM STANDARD-SET

with steel cage incl. new double run-out system

Item no.: 10054 | 10056 | 10058 | 10048 | 10051



**VIDEO**

Fiberglass rod  
Ø 4,5 mm

[Click here Video](#)

[Click here Productinformation](#)

**Detailed images:**

All steel cages are equipped with a lateral locking brake and the new double run-out system (quick outlet and automatic run-out brake)

Quick run with rollers

automatic run-out brake

**BEGINNING**

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

**ENDING**

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

**Achtung!**  
Stromleitend  
**Attention!**  
electric  
conductive

DATA					
ITEM NO.	10054	10056	10058	10048	10051
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	fur tube diameter von 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

- ADVANTAGES**
- ✓ incl. steel reel
  - ✓ Double run-out system (automatic run-out brake and fast run-out)
  - ✓ Additional parking brake
  - ✓ Glass fibre rod total breaking load up to 1300 kg
  - ✓ Total breaking load 220 kg  
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

**DESCRIPTION**

Standard set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

**Optimal field of application:** for pipe diameters 30 mm - 80 mm.

**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).

**Scope of delivery:** 1 piece fiberglass rod Ø 4.5 mm Standard Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end

**INFORMATION**

**Compatible with:**

**RUNPOCAM RC2**

Length: 10 m | 30 m | 50 m  
Item no. 10139 | 10140 | 10141

[Click here Productinformation](#)