

# Valena™ Life


## TV sockets with cover plate




7 533 52 + 7 541 31  
(Aluminium)



7 531 61 + 7 540 01  
(White)



7 531 64 + 7 540 81  
(Lime)



7 532 64 + 7 541 81  
(Light wood)

Valena In'Matic mechanisms supplied with cover plates and support frames. To be equipped with plates  
Supplied with mounted dust protection transparent shield  
Flowpack packaging: robust protection to ensure optimum operation

Pack	Cat.Nos	Star architecture TV sockets
		<p>For DVBT, Cablecast and satellite installation UHD TV compatible Class A shielded star socket LTE Ready (4G protected) Recommended coaxial cable: 17 VATC Star cabling (1 socket = 1 cable to antenna, splitter or multiswitch) Visual check of the connection Meet EN 50083-4 and EN 50083-2 European directive TV male connector (Ø9.5 mm): 0-862 MHz R female connector (Ø9.5 mm): 87.5 - 108 MHz SAT "F" type connector: 950-2400 MHz</p> <p><b>TV-R-SAT sockets</b> Low attenuation: 1.5 dB</p>
5	7 531 52	White
5	7 532 52	Ivory
5	7 533 52	Aluminium
		<p><b>Male TV sockets</b> Low attenuation: 1 dB</p>
5	7 531 51	White
5	7 532 51	Ivory
5	7 533 51	Aluminium

Pack	Cat.Nos	Passthrough TV sockets - 10 dB
		<p>Installation in case of maintenance An amplifier and line balancing are recommended TV male connector (Ø9.5 mm): 5-68/120-862 MHz R female connector (Ø9.5 mm): 87.5 - 108 MHz SAT "F" type connector: 950-2400 MHz Visual check of the connection</p> <p><b>TV-R-SAT sockets</b> Attenuation: 14 dB</p>
5	7 531 65	White
5	7 532 65	Ivory
5	7 533 65	Aluminium
		<p><b>Male TV sockets</b> Attenuation: 14 dB</p>
5	7 531 61	White
5	7 532 61	Ivory
5	7 533 61	Aluminium
		<p><b>Terminal TV sockets</b> Installation in case of maintenance An amplifier and line balancing are recommended TV male connector (Ø9.5 mm): 5-68/120-862 MHz R female connector (Ø9.5 mm): 87.5 - 108 MHz SAT "F" type connector: 950-2400 MHz Recommended coaxial cable: Visual check of the connection 1 input with 1 resistance cap socket -10 dB</p> <p><b>TV-R-SAT sockets</b> Attenuation: 10 dB</p>
5	7 531 64	White
5	7 532 64	Ivory
5	7 533 64	Aluminium
		<p><b>Male TV sockets</b> Attenuation: 10 dB</p>
5	7 531 60	White
5	7 532 60	Ivory
5	7 533 60	Aluminium