



VCF 0GE



VCF 3GE



VCF 5GEN



VCFN 12GE

Enclosed switch-disconnectors for high performance applications

- 3-pole rotary switch-disconnectors, 10 to 140 A, conforming to IEC 60947-4-1 and IEC 60204.
- Marking on operator $\circ \downarrow$.
- Padlockable operating handle (padlocks not included).
- IP 65 degree of protection enclosures, sealable and lockable.
- Cover lockable in position "I" (ON) up to 63 A rating.
- Ground plate for shielded cable continuity ($\varnothing 11$ to 14 mm) on enclosed switch-disconnectors "GP" version.

3-pole main and Emergency Stop switch-disconnectors ⁽¹⁾								
Operator Handle	Front plate Dimensions	Ithe	Power AC-23 at 400 V	Incorporated switch body	Possible attachments ⁽²⁾	With ground plate	Reference ⁽³⁾	Weight
	mm	A	kW					kg
Red, standard, padlockable with up to 3 padlocks ($\varnothing 4$ to $\varnothing 8$ shank)	Yellow 60 x 60	10	4	V02	2	No	VCF02GE	0.400
		16	5.5	V01	2	Yes	VCF02GEGP	0.460
		20	7.5	V0	2	No	VCF01GE	0.400
		25	11	V1	2	Yes	VCF01GEGP	0.460
		32	15	V2	2	No	VCF02GE	0.500
		50	22	V3	3	No	VCF3GE	0.930
Red, long, padlockable with up to 3 padlocks ($\varnothing 4$ to $\varnothing 8$ shanks)	Yellow 90 x 90	100	37	V5	1	No	VCF5GEN	2.190
		140	45	V6	1	No	VCF6GEN	2.190

3-pole main switch-disconnectors ⁽¹⁾								
Operator Handle	Front plate Dimensions	Ithe	Power AC-23 at 400 V	Incorporated switch body	Possible attachments ⁽²⁾	With ground plate	Reference ⁽³⁾	Weight
	mm	A	kW					kg
Black, standard, padlockable with up to 3 padlocks ($\varnothing 4$ to $\varnothing 8$ shank)	Black 60 x 60	10	4	V02	2	No	VBF02GE	0.500
		16	5.5	V01	2	Yes	VBF01GE	0.500
		20	7.5	V0	2	No	VBF00GE	0.500
		25	11	V1	2	Yes	VBF01GE	0.500
		32	15	V2	2	No	VBF02GE	0.500
		50	22	V3	3	No	VBF3GE	0.930
Black, long, padlockable with up to 3 padlocks ($\varnothing 4$ to $\varnothing 8$ shank)	Black 90 x 90	100	37	V5	1	No	VBF5GEN	2.190
		140	45	V6	1	No	VBF6GEN	2.190

Enclosed switch-disconnectors for standard applications

- 3-pole rotary switch-disconnectors, 10 to 32 A, conforming to IEC 60947-4-1.
- Degree of protection IP 55.

3-pole main and Emergency Stop switch-disconnectors ⁽¹⁾								
Operator Handle	Front plate Dimensions	Ithe	Power AC-23 at 400 V	Incorporated switch body	Possible attachments ⁽²⁾	With ground plate	Reference ⁽³⁾	Weight
	mm	A	kW					kg
Red padlockable, either by 1 ($\varnothing 8$ shank) or by 3 padlocks ($\varnothing 6$ shank)	Yellow 60 x 60	10	4	VN 12	2	No	VCFN12GE ⁽²⁾	0.422
		16	5.5	VN 20	2	No	VCFN20GE ⁽²⁾	0.422
		20	7.5	V0	0	No	VCFN25GE	0.512
		25	11	V1	0	No	VCFN32GE	0.512
		32	15	V2	0	No	VCFN40GE	0.512

⁽¹⁾ For characteristics of switch-disconnectors, please consult your Regional Sales Office.

⁽²⁾ For VCF and VBF enclosures, see page A1/4. For VCFN enclosures, see page A1/5.


⁽³⁾ Enclosure not suitable in atmosphere contaminated with harsh substances (detergents, chlorine solvents, ketones, alcohol, aromatic hydrocarbons).

Note: For VCF and VBF enclosures from 02GE to 2GE, only one auxiliary contact block VZ7 or VZ20 can be mounted.


TeSys protection components

VARIO switch-disconnectors for high performance applications

Complete units

- 3-pole rotary switch-disconnectors, 12 to 175 A
- Marking on operator 
- Padlockable operating handle (padlocks not supplied).
- Degree of protection IP 65.

Switch-disconnectors



VCF 0



VCF 5



VCCF 0

Main and Emergency stop switch-disconnectors for door mounting

Handle	Front plate mm	Fixing	Rating A	Reference	Weight kg
Red, padlockable with up to 3 padlocks (Ø4 to Ø8)	Yellow 60 x 60	Ø22.5	12	VCD02	0.215
			20	VCD01	0.215
			25	VCD0	0.215
			32	VCD1	0.215
			40	VCD2	0.215
4 screws			12	VCF02	0.250
			20	VCF01	0.250
			25	VCF0	0.250
			32	VCF1	0.250
			40	VCF2	0.250
			63	VCF3	0.560
Red, long, padlockable with up to 3 padlocks (Ø4 to Ø8)	Yellow 90 x 90	4 screws	125	VCF5	1.200
			175	VCF6	1.200

Main and Emergency stop switch-disconnectors for mounting at back of an enclosure ⁽¹⁾

Handle	Front plate mm	Fixing	Rating A	Reference	Weight kg
Red, padlockable with up to 3 padlocks (Ø4 to Ø8)	Yellow 60 x 60	Ø22.5	12	VCCD02	0.392
			20	VCCD01	0.392
			25	VCCD0	0.392
			32	VCCD1	0.392
			40	VCCD2	0.392
4 screws			12	VCCF02	0.527
			20	VCCF01	0.527
			25	VCCF0	0.527
			32	VCCF1	0.527
			40	VCCF2	0.527
			63	VCCF3	0.440
Red, long, padlockable with up to 3 padlocks (Ø4 to Ø8)	Yellow 90 x 90	4 screws	125	VCCF5	1.320
			175	VCCF6	1.320

⁽¹⁾ Unit supplied with a shaft extension **VZN 17** or **VZ18** and a door interlock plate **KZ 32** or **KZ 74** (see page B3/14).