



ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: **43-134-15**

Valid from: 2023 06 20
until: 2024 04 16

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: **PC Electric Ges.m.b.H.**
Diesseits 145
4973 St. Martin im Innkreis
Austria

Product: **Rewirable portable socket outlet with side earthing contact**

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s): **TGM-VA EE 37979A, TGM-VA EE 37979, TGM-VA EE 35727A, TGM-VA EE 35727**

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

T. Neumayer
Digitally signed by T. Neumayer
Email=t.neumayer@ove.at



Wien, 2023 06 20

Dipl.-Ing. T. Neumayer

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



Manufacturer:

PC Electric Ges.m.b.H.
Diesseits 145
4973 St. Martin im Innkreis
Austria

Factory location(s):

PC Electric Ges.m.b.H.
Diesseits 145
4973 St. Martin im Innkreis
Austria

Tested and certified according to:

ÖVE/ÖNORM IEC 60884-1:2005-09-01
ÖVE/ÖNORM E 8684-1:2010-03-01
DIN VDE 0620-2-1:2016-01

Product: Rewirable portable socket outlet with side earthing contact

Type designation:

Rating:

Trademark:

25..

Rated voltage: AC 250 V
Rated current: 16 A
IP20 or IP54
see typecode

PCE / ELCEE

256..

Rated voltage: AC 250 V
Rated current: 16 A
IP20 or IP44
see typecode

PCE / ELCEE

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

Typecode

| | | | | | | |
|--|----------|----------|----------|----------|----------|----------|
| 25 | 1 | 0 | - | s | s | c |
| Shutter | | | | | | |
| blank | | | | | | |
| Without Shutter | | | | | | |
| c | | | | | | |
| with Shutter (only with contact carrier PA6) | | | | | | |
| Colour hexagonal ring (only for types with internal cord anchorage) | | | | | | |
| r | | | | | | |
| red | | | | | | |
| he | | | | | | |
| yellow | | | | | | |
| s | | | | | | |
| black | | | | | | |
| o | | | | | | |
| orange | | | | | | |
| b | | | | | | |
| blue | | | | | | |
| hb | | | | | | |
| lightblue | | | | | | |
| u | | | | | | |
| green RAL 6031 F9 | | | | | | |
| hu | | | | | | |
| fluorescent green | | | | | | |
| su | | | | | | |
| siemensgreen | | | | | | |
| g | | | | | | |
| grey | | | | | | |
| dg | | | | | | |
| darkgrey | | | | | | |
| w | | | | | | |
| white | | | | | | |
| a | | | | | | |
| anthracite | | | | | | |
| * | | | | | | |
| reserved for different colours | | | | | | |
| Colour housing part | | | | | | |
| s | | | | | | |
| black | | | | | | |
| e | | | | | | |
| yellow | | | | | | |
| r | | | | | | |
| red | | | | | | |
| o | | | | | | |
| orange | | | | | | |
| b | | | | | | |
| blue | | | | | | |
| u | | | | | | |
| green | | | | | | |
| g | | | | | | |
| grey | | | | | | |
| a | | | | | | |
| anthracite | | | | | | |
| * | | | | | | |
| reserved for different colours | | | | | | |
| Customer type | | | | | | |
| - | | | | | | |
| PCE | | | | | | |
| Degree of protection | | | | | | |
| 0 | | | | | | |
| IP20 (without lid) | | | | | | |
| 1 | | | | | | |
| IP44 or IP54 (lid captive strip) | | | | | | |
| 2 | | | | | | |
| IP44 oder IP54 (hinged lid) | | | | | | |
| Contact carrier | | | | | | |
| 1 | | | | | | |
| PA6 lightgrey (internal cord anchorage, without Shutter) black (internal cord anchorage, with Shutter) black (external cord anchorage) | | | | | | |
| 2 | | | | | | |
| TPE anthracite (internal/external) cord anchorage) | | | | | | |
| 3 | | | | | | |
| PA6 black (internal cord anchorage, without Shutter) | | | | | | |
| Basic type | | | | | | |
| 25 | | | | | | |
| with internal cord anchorage | | | | | | |
| 256 | | | | | | |
| with external cord anchorage | | | | | | |

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.