15.11.19 | 0002 01.01.2017 | 0001

Cable lubricant SPRAY 400 ml | Item no.: 20523



SAFETY DATA SHEET

ACCORDING TO ANNEX II TO REACH - REGULATION 2015/830

SECTION 1.

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Cable lubricant Spray 400 ml - Item number 20523

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use: Silicone oil to reduce the friction during electrical cable installation

1.3 Details of the supplier of the safety data sheet

RUNPOTEC GmbH | Irlachstraße 31 | A-5303 Thalgau Tel.: +43-6235-20335 | Fax: +43-6235-20335-35 office@runpotec.com | www.runpotec.com

1.4 Emergency telephone number

Emergeny information services / public advisory office:

AUSTRIA: Veraiftungsinformationszentrale der Gesundheit Österreich GmbH, Wien.

NOTRUF Tel.: 01 406 43 43 (von außerhalb Österreichs Tel.: +43 1406 43 43)

Switzerland: Tox Info Suisse, Freiestrasse 16, CH-8032 Zürich. Nationale 24h-Notfallnummer: 145

SECTION 2. HA7ARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol category 3 H229 Pressurised container: may burst if heated

2.2 Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements

Hazard pictogramms: ---

Signal words: Achtung

Hazard statements:

H229 Pressurised container: may burst if heated

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C /

122°F

2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019

Cable lubricant SPRAY 400 ml | Item no.: 20523



SECTION 3. Composition/information on ingredients

3.2 Mixtures

Contains:

Identification x=Conz. % Classification 1272/2008 (CLP)

Carbon Dioxide

CAS 124-38-9 4 > x < 4.5 Substance with a community workplace exposure limit

EC 204-696-9

Index -

Propylene carbonate

CAS 108-32-7 1 < x < 1,5 Eye Irrit. 2 H319

EC 203-572-1 Index 607-194-00-1

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 4,00 %

SECTION 4. First aid measures

4.1 Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown

4.3 Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

15.11.19 | 0002 01.01.2017 | 0007 RUNPOTEC*
STRONGEST CABLE PULLING

Cable lubricant SPRAY 400 ml | Item no.: 20523

5.3 Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures

6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water

6.3 Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray

7.2 Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3 Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Regulatory References:

DEU Deutschland TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Ar

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019



Cable lubricant SPRAY 400 ml | Item no.: 20523

ESP	España	beitsplatzgrenzwerte und Kurzzeitwerte INSHT - Límites de exposición profesional para agentes químicos en España 2017
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΌΣ ΠΡΩΤΌ Αρ.
		Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Datenbank des Wirtschafts- und Sozialrates der Nieder lande (SER) Values, AF 2011:18
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
EU	OEL ĔU	Richtlinie (EU) 2017/2398; Richtlinie (EU) 2017/164; Richtlinie
		2009/161/EU; Richtlinie 2006/15/EG; Richtlinie 2004/37/EG; Richtli
		nie 2000/39/EG; Richtlinie 91/322/EWG.
	TLV-ACGIH	ACGIH 2018

CARBON DIOXIDE							
Threshold Limit Value							
TYPE	COUNTRY	TWA/8 h		STEL/15 min	STEL/15 min		
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	9100	5000	18200	10000		
MAK	DEU	9100	5000	18200	10000		
VLA	ESP	9150	5000				
WEL	GBR	9150	5000	27400	15000		
TLV	GRC	9000	5000	54000	5000		
VLEP	ITA	9000	5000				
OEL	NLD	9000	5000				
MAK	SWE	9000	5000	18000	10000		
OEL	EU	9000	5000				
TLV-ACGIH		9000	5000	54000	30000		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction

8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type B filter combined with a type P filter should be worn (see standard EN 14387). Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment,

Revised on | Version: Replace version dated | Version:

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019 Valid from



Cable lubricant SPRAY 400 ml Item no.: 20523

should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance aerosol Colour colourless Odour odourless Not available Odour threshold Not available Melting point / freezing point < -10 °C Initial boiling point Not available Boiling range Not available Flash point > 100 °C **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit Not available Not available Upper inflammability limit Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 0.97 Solubility Not available

Partition coefficient: n-octanol/water Not available Not available Auto-ignition temperature Decomposition temperature Not available Viscosity Not available Explosive properties Not available

Oxidising properties Not available

9.2 Other information

Total solids (250°C / 482°F) 100,00 % VOC (Directive 2010/75/EC): 0

VOC (volatile carbon): 0

SECTION 10 Stability and reactivity

10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use

10.2 Chemical stability

The product is stable in normal conditions of use and storage

10.3 Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4 Conditions to avoid

Avoid overheating.

10.5 Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material

10.6 Hazardous decomposition products

Information not available

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019

Cable lubricant SPRAY 400 ml | Item no.: 20523



SECTION 11 Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

METABOLISM, TOXICOKINETICS, MECHANISM OF ACTION AND OTHER INFORMATION

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019

Cable lubricant SPRAY 400 ml | Item no.: 20523



SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation

12.1 Toxicity

Information not available

12.2 Persistence and degradability

Information not available

12.3 Bioaccumulative potential

Information not available

12.4 Mobility in soil

Information not available

12.5 Results of PBT and vPvB assessment

Die Stoffe im Gemisch erfüllen nicht die PBT-/vPvB-Kriterien gemäß REACH-Verordnung, Anhang XIII.

12.6 Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1 UN-number

ADR/RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR/RID: AEROSOLE IMDG: AEROSOLE

IATA: AEROSOLE, Non-flammable

14.3. Transportgefahrenklasse(n):

ADR / RID: Class 2 Label: 2.2

IMDG: Class 2 Label: 2.2

IATA: Class 2 Label: 2.2

14.4. Packing group

ADR/RID, IMDG, IATA -

Safety Data Sheet according to Annex II to REACH - Regulation 2015/830

Revised on | Version: 15.11.19 | 0002

01.01.2017 | 0001 15.11.2019 Replace version dated | Version: Valid from



Cable lubricant SPRAY 400 ml | Item no.: 20523

14.5 Environmental hazards

ADR / RID: No IMDG: No IATA: No

14.6 Special precautions for user

ADR /RID:	HIN - Kemler:	Limited Quantities: 1 L	Tunnel restriction code: (E)
	Special Provision: -: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions	A98, A145, A167, A802	

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Information not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.11.19 | 0002 01.01.2017 | 0001 15.11.2019

Cable lubricant SPRAY 400 ml | Item no.: 20523



15.2 Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Aerosol 3 Aerosol, category 3 Eye Irrit. 2 Eye irritation, category 2

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)

Safety Data Sheet according to Annex II to REACH - Regulation 2015/830

 Revised on | Version:
 15.11.19 | 0002

 Replace version dated | Version:
 01.01.2017 | 0001

 Valid from
 :
 15.11.2019



Cable lubricant SPRAY 400 ml | Item no.: 20523

- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.