







Szigetelt villássaru

TRACON	d ₁ (mm)	d ₂ (mm)	D (mm)	L (mm)	l (mm)	B (mm)	mm ²			
										
PV3	1.7	3.7	5.4	21.5	6.4	6.3	1.5	1.5	0.75-1	
PV4	1.7	4.3	5.4	21.5	6.6	7.1	1.5	1.5	0.75-1	
PV5	1.7	5.3	5.4	22.5	7.6	7.9	1.5	1.5	0.75-1	
PV6	1.7	6.6	5.4	25.5	8.7	10.8	1.5	1.5	0.75-1	
KV3	2.3	3.6	6.1	22.7	6.6	6.2	2.5-4	1.5-2.5	1.5-2.5	
KV4	2.3	4.3	6.1	22.7	7.1	7.1	2.5-4	1.5-2.5	1.5-2.5	
KV5	2.3	5.3	6.1	23	7.6	7.9	2.5-4	1.5-2.5	1.5-2.5	
KV6	2.3	6.6	6.1	26.5	8.7	10.7	2.5-4	1.5-2.5	1.5-2.5	
SV3	3.4	3.6	8	26.5	7.3	7.2	6	4-6	4	
SV4	3.4	4.3	8	27.3	7	8.1	6	4-6	4	
SV5	3.4	5.3	8	27.3	7.4	9	6	4-6	4	
SV6	3.4	6.4	8	30.3	9.2	10.8	6	4-6	4	

9006; 9006R;
9006RS

RELEVANT STANDARD
MSZ-05-45.1601-22
MSZ-05-45.1601-1



B/6

Ajánlott prészerszámok:

TRACON	mm ²
LY35C	10-35
9006RS	0.5-2.5
9006R	2.5-6
9006	2.5-6

