

Product datasheet

Specifications



extension ETL - 2P - 1C/O + 1NO -
16A - coil 110 VDC - 230...240VAC
50/60Hz

15530

❗ Discontinued on: 17 November 2014

❗ End-of-service on: 01 April 2019

❗ Discontinued

Main

| | |
|---------------------------|-----------------------------|
| Product or component type | Extension for impulse relay |
| Device short name | ETL |
| Relay application | Remote control |
| Poles description | 2P |
| Pole contact composition | 1 C/O + 1 NO |
| [In] rated current | 16 A |
| Network type | AC |

Complementary

| | |
|--------------------------------|--|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Control type | Remote control Toggle |
| Control signal type | Impulse |
| Switching frequency | 5 switching operations/minute |
| Impulse duration | 50 ms |
| Remote control type | Illuminated push-button 3 mA |
| Local signalling | ON/OFF indication |
| [Uc] control circuit voltage | 230...240 V AC 50/60 Hz 110 V DC |
| Supply inrush power | 19 VA |
| Mounting mode | Fixed, on right side of TL |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 2 |
| Height | 84 mm |
| Width | 18 mm |
| Depth | 60 mm |
| Colour | Grey |
| Electrical durability | AC-21: 200000 cycles AC-22: 100000 cycles |

| | |
|-------------------------------|---|
| Connections - terminals | Tunnel type terminals - <= 10 mm² |
| Auxiliary connection terminal | Tunnel type terminalscontrol circuit in 0.5...6 mm² |

Environment

| | |
|---------------------------------------|-----------------------------------|
| Standards | EN 669-1 EN 669-2-2 |
| Product certifications | GOST VDE CEBEC IMQ NF |
| Noise level | 60 dB |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -20...50 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8 cm |
| Package 1 Width | 3 cm |
| Package 1 Length | 8.5 cm |
| Package 1 Weight | 0.124 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)

15530 is replaced by:

1x



Acti9, Extension iETL iTL 16- 2P - 1C/O+1NO -16A - coil 110VDC - 230...240V AC 50/60Hz
A9C32816