

Valena™ Life

IP44 devices with white cover plate



7 521 61 + 7 540 71
(Terracotta)



7 521 59 + 7 540 81
(Lime)



7 531 19 + 7 540 01
(White)



7 521 77 + 7 540 81
(Lime)



7 540 21

Valena In'Matic mechanisms supplied with white cover plates, weatherproof membrane and support frames
To be equipped with plates. Supplied with mounted dust protection transparent shield
Flowpack packaging: robust protection to ensure optimum operation

Pack	Cat.Nos	Switches 10 AX - 250 V~	Pack	Cat.Nos	Push-buttons 6 A - 250 V~
5	7 521 51	Automatic terminals One-way switch □ White	5	7 521 71	Automatic terminals Changeover push-button □ White
5	7 521 56	Two-way switch □ White	5	7 521 75	Changeover push-button, bell symbol □ White
5	7 521 61	Illuminated one-way switch Equipped with 0.15 mA low consumption LED Cat.No 0 676 84 □ White	5	7 521 76	Illuminated changeover push-button, bell symbol Equipped with 0.15 mA low consumption LED Cat.No 0 676 84 □ White
5	7 521 67	Illuminated two-way switch Equipped with 0.15 mA low consumption LED Cat.No 0 676 84 □ White			2P+E sockets with shutters, with flap 16 A - 250 V~
5	7 521 55	2-gang one-way switch □ White	5	7 531 19	Automatic terminals German standard □ White
5	7 521 58	2-gang two-way switch □ White			Motion sensor without neutral 250 W IP 44 Compatible with any type of lamp Detection field 120° Detection range 8 m Integrated self-protection against overloads and short-circuits Screw terminals Accepted power by lamp type: - LEDs ¹ 3 W to 100 W - Compact fluorescent ¹ 3 W to 100 W - LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to 250 VA - 230 V halogen, incandescent: 3 W to 250 W Up to 3 sensors can be connected in parallel Time delay setting from 10 s to 10 min. Light level threshold setting from 5 lux to 1275 lux. Standby consumption: 0.02 W □ White
1	7 521 59	Illuminated 2-gang two-way switch Equipped with 2 PCS 2 x 0.15 mA low consumption LED Cat.No 0 676 84 □ White	1	7 521 77	□ White
5	7 521 64	Double pole switch 16 AX - 250 V~ Screw terminals □ White			IP 44 plate with flap Compatible with all Valena Life mechanisms IP 44 / IK 07 UV-resistant

1: if several sensors are installed on the same circuit, the minimum load increases (see data sheet)